





NEW CONSTRUCTION WINDOWS

PETOW PICTURE WINDOW

the **CORE**
window & door platform products by VEKA



PE101
MASTER FRAME



SH1019
T-MULLION



BV64
GLAZING BEAD
3/16" GLASS



BV50
GLAZING BEAD
3/4" GLASS



BV51
GLAZING BEAD
3/4" GLASS

FEATURES & BENEFITS

- Grade 35 performance.
- Exterior frame bevel.
- 3/4" glass package.
- Full 1" integral nailfin.
- Exterior glazed.
- Multi-chambered heavy wall frame for less roll.
- 1-3/8" fin set back.
- Optional two piece field mulling system.
- Full family of Single Hung, Single Slider, and Picture Window.

MFG. LIMITATIONS

Minimum *

Maximum 40 ft²

* Minimum sizes are determined by process machinery capabilities.

BASELINE PERFORMANCE

Thermal Insulation

GLASS	Uc Value	R Value
Low-E/Argon/Dual	.27	3.70
Double Low-E/Argon	.22	4.55
Double Low-E/Krypton	.19	5.26

Structural Performance

Air Infiltration@ 25MPH	.01 cfm/ft ²
Water Penetration	7.5 psf
Uniform Loads	+/- 52.5 psf

AAMA RATING: CW-PG35-FW



ASSEMBLIES

